

Delta4 HexaMotion 6D Motion Management QA





CONFIDENCE | SAFETY | ACCURACY | EFFICIENCY



Your Ideal Solution for Motion Management QA

HexaMotion is a motion platform that recreates the movement of the tumor in six dimensions^{*} and independently simulates patient breathing motion. Together with Delta4 Phantom+, it ensures tumor control in moving targets and answers the vital questions:

- Am I hitting the target?
- What do I gain with tumor tracking or gating?

*Longitudinal, lateral, height, roll, tilt, and time.



With HexaMotion, you can check and verify the effects of intra-fractional motions of the tumor and OAR.

THE TUMOR MOVES AND SO DOES THE HEXAMOTION

Intra-fractional movements of the tumor can cause large geometrical errors. This is especially true for tumors in the lung and the liver, it has been shown that even the prostate can move considerably during the treatment. If these geometrical errors are not handled correctly they can result in critical dosimetric errors. This may result in the tumor volume receiving too little dose to achieve tumor control whilst organs at risk can recieve too high dose.

Techniques such as gating and tumor tracking are good at addressing these issues. However, to ensure the best possible treatment outcome, they require a special QA system that can recreate target movements. With HexaMotion, you cancheck and verify the effects of intra-fractional motions of the tumor and OAR.

100 CTV 80 Relative Volume (%) Rectum 60 40 20 Planned -- Delivered Tracking 0 10 70 80 30 40 50 60 90 100 110 20 Relative Dose (%)

TREAT WHAT YOU INTEND TO TREAT

Graph, images, and data courtesy of the University of Sidney and the Royal North Shore Hospital, Sydney, Australia.

Use Real Tumor Motion

The HexaMotion 6D motion platform accuracely replicates the actual tumor motion. The QA is based on how the real tumor is moving. The motion patterns both for the tumor and the patient can be imported from your motion management system and the same movement cycle is then exactly reproduced with the Delta4 Phantom+. The phantom is positioned quickly and within sub-millimeter accuracy.

The new Independent Motion Platform option for the HexaMotion is developed in close collaboration with linac manufacturers, and its purpose is to mimic the breathing of the patient independent of the motion of the tumor.

FIND OUT WHEN MOTION MANAGEMENT IS REQUIRED

The HexaMotion 6D motion platform is used together with the Delta4 Phantom+ to provide a full analysis of the dosimetric effect of tumor respiratory motion. The true delivery of the prescription dose can be studied in detail for each patient and critical structure, allowing the clinician to easily identify which patients or which groups of patients require motion management.

VALIDATE THE COMPLETE DELIVERY CHAIN

The complete motion management QA process shall examine the entire delivery system, including accelerator, MLC control, the motion detection and the gating or tracking system. The Hexamotion system allows the user to scrutinize:

- Monitor system start and stop
- Latencies in the delivery system
- Beam hold for anomalous conditions
- Beam hold if target exceeds threshold
- Correctness of the coordinate systems
- Baseline shifts
- End-to-end dosimetric effect



MOTION RESULTS



Absolute dose and gamma index <u>without</u> motion compensation.



Absolute dose and gamma index with motion compensation.

Streamlined Workflow

HexaMotion together with the Delta4 Phantom+

The system is placed on the treatment table, where it measures the same geometric points throughout the entire delivery. It only takes one measurement and the complete delivery sequence is acquired—becoming immediately available for analysis. The measured dose is then compared to the calculated data from the treatment planning system (TPS). With customizable acceptance criteria and an instant display of results, it's easy to see whether the verification of the delivery has passed or failed.

Next, the motion pattern from the patient is imported into the HexaMotion software. The motion pattern can come from 4D-CT, ExacTrac or similar. The HexaMotion then mimics the movement of the actual target.

Delta4 Phantom+ measures the 3D dose distribution during the delivery of the plan, and shows exactly where the dose ends up.



Quick and easy setup

- Trolley eliminates all lifting
- System slides from trolley to treatment table
- Remote-controlled alignment of the system
- Delivery verified with one measurement



Easy analysis and intuitive software

- Fully automated
- Instant results in one place
- Powerful analytic tools
- Clear and modifiable reporting

The Delta4 Phantom+ with Hexamotion helps me feel assured that my machine can deliver the dose that is promised to the patient, that it is done safely, and I get fantastic results from it.

Aaron A. Kempenich MSc, DABR, Medical Physicist and radiation safety officer, Altru Cancer Center, Grand Forks, ND

We drive the development of solutions for safer radiation therapy

Technical Specifications

HEXAMOTION

Positioning accuracy Movement range

Refresh rate

Total weight

Better than 0.5 mm **X:** +/- 40 mm, **Y:** +/- 40 mm, **Z:** +/- 40 mm **Roll**: +/- 100 @ origin, **Tilt**: +30/-60 @ origin 50 Hz 17 kg

Trolley provides easy and ergonomical handling of the system eliminating heavy lifts

INDEPENDENT MOTION PLATFORM (optional)

Positioning accuracy Movement range Total weight Better than 0.5 mm **Z:** +/- 40 mm, vertical movement only 3 kg

DELTA4 PHANTOM+

Cylinder Phantom

Material PMMA Diameter 22 cm Length 40 cm Total Length 71 cm Total Weight 27 kg

Ion chamber insert in cylinder Inserts for common cylindrical ion chambers available

Detectors

Type p-Si **Total number** 1069 Layout Distributed on coronal and sagittal plane **Max field size** 20 x 38 cm² (when merging two consecutive measurements, otherwise 20 x 20 cm²)

Distance between detectors

Central area (6 x 6cm²) 5 mm (or 2.5 mm in longitudinal direction with merging of two consecutive measurements) **Outer area** 10 mm **Size (radial x axial)** 1 x 0.05mm³= 0,00004 cm³ **Detector stability (6MV beam)** Better than 0.1% per kGy, typically 0.04%/kGy

Wireless Communication

Wireless data communication protocol Wi-Fi 802.11n **Battery operation capacity** >4 hours Rechargeable Li-ion battery – power supply for charging included

Compatibility

Modalities Photon beams, with and without flattening filter

Treatment plan import Any treatment planning system that can export DICOM RT plan, RT Dose, and RT Structure







The HexaMotion platform allowed for accurate phantom positioning and motion for a wide range of simple and realistic patient motions. The Delta4 Phantom+ was found to be very reliable, easy to setup and allowed for easy analysis of dose delivery accuracy.

Lee Goddard Medical Physicist, DABR, Montefiore Medical Center, Bronx, NY

Innovative and Efficient QA delta4family.com



Corporate Headquarters

ScandiDos AB (publ) Uppsala Science Park SE-751 83 Uppsala, Sweden +46 18 472 3030 info@scandidos.com delta4family.com

in scandidos

© Copyright ScandiDos AB

China	Beijing ScandiDos Technology Ltd. Co. sales-china@scandidos.com
France	ScandiDos SAS sales-france@scandidos.com
USA	ScandiDos Inc sales-us@scandidos.com